

WHAT IS CLAIMED IS:

Sub
a1

1. An image processing apparatus, comprising:
generating means for generating a map having a
symbol indicating an installed position of a camera;
5 receiving means for receiving the image data
corresponding to an image picked up by the camera
associated, when the information regarding the camera
including the position of camera is associated with the
map; and
10 output means for outputting the received image
data onto a display.
2. The image processing apparatus according to
claim 1, wherein said information regarding the camera
15 includes the information of the direction of camera.
3. The image processing apparatus according to
claim 1, wherein the position of the symbol
corresponding to the camera on the map is determined in
20 accordance with said information regarding the camera.
4. The image processing apparatus according to
claim 2, wherein the direction of the symbol
corresponding to the camera on the map is determined in
25 accordance with the information regarding the camera.
5. The image processing apparatus according to

09626815-072700

claim 1, further comprising control means for controlling a camera corresponding to the symbol in response to an operation on the symbol.

5 6. The image processing apparatus according to claim 1, wherein the data input for association is performed by a manual instruction of the operator.

10 7. The image processing apparatus according to claim 6, further comprising display means for displaying the image data, the data input being performed on the display means.

15 8. An image processing method, comprising the steps of:

generating a map having a symbol indicating an installed position of a camera;

20 receiving image data corresponding to an image picked up by the camera associated, when the information regarding the camera including the position of camera is associated with the map; and

outputting the received image data onto a display.

25 9. A storage medium readable by a computer, wherein the storage medium stores:

a code for generating a map having a symbol indicating an installed position of a camera;

a code for receiving the image data corresponding to an image picked up by the camera associated, when the information regarding the camera including the position of camera is associated with the map; and

5 a code for outputting the received image data onto a display.

10 10. An image processing apparatus, comprising:
input means for inputting an identification name of a camera connected to a network and connection information;

15 receiving means for receiving tentatively image data from he said camera in accordance with the connection information, and based on the connection information; and

output means for outputting the identification name of the camera and the connection information onto a display.

20 11. The image processing apparatus according to claim 10, wherein the connection information of the camera includes an Internet protocol address of the camera.

25 12. The image processing apparatus according to claim 10, wherein said receiving means performs the tentative reception automatically after the input means

09626815-072700

accepts the input.

13. The image processing apparatus according to
claim 10, wherein the output to the display is not
5 ended without confirming instruction of an operator.

14. The image processing apparatus according to
claim 12, wherein at least one instruction of the pan,
tile and zoom conditions is automatically output to a
10 camera in accordance with the connection information,
in performing the automatic reception, to receive an
image of the camera in stated conditions.

15. The image processing apparatus according to
15 claim 10, wherein at least one of the pan, tile and
zoom of the camera is changeable in accordance with an
instruction on the display, in performing the tentative
reception of the image data, the image data received
tentatively being variable.

20 16. An image processing method, comprising the
steps of:

inputting an identification name of a camera
connected to a network and connection information;
25 receiving tentatively the image data from the
camera in accordance with the connection information,
and based on the connection information; and

09626815-072700

outputting the identification name of the camera
and the connection information onto a display.

17. A storage medium that stores:

5 a code for inputting an identification name of a
camera connected to a network and connection
information;

10 a code for receiving tentatively the image data
from the camera in accordance with the connection
information, and based on the connection information;
and

15 a code for outputting the identification name of
the camera and the connection information onto a
display.

09626815.072700